## HellermannTyton

## 117-00018

117-00018	
Art	icle Number: 117-00018
Do	uble Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 100/pkg
	r RoHS
Download drawing Download	spec sheet
Local Order Number	117-00018
Туре	T50SDH
Color	Black (BK)
Features and Benefits	<ul><li>Design allows the fastening of two separate bundles.</li><li>The tie's second loop may can serve as a positioning device for a single bundle.</li></ul>
Product Description	The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Double Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 100/pkg

## **Product Dimensions**

Minimum Tensile Strength (Imperial)	50.0 lbs	
Minimum Tensile Strength (Metric)	225.0 N	
Length L (Imperial)	6.3 "	
Length L (Metric)	159.0 mm	
Fixation Method	None	
Identification Plate Position	none	
Releasable Closure	No	
Variant	Inside Serrated	
Width W (Imperial)	0.19 "	
Width W (Metric)	4.7 mm	
Bundle Diameter Min. (Imperial)	0.06 "	
Bundle Diameter Min. (Metric)	1.6 mm	
Bundle Diameter 1st Loop Max.		
(Imperial) Bundle Diameter 1st Loop Max. (Metric)35.0 mm		

## Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100
Carton Quantity	5000

**Material and Specifications** 

Material Shortcut	PA66
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
<b>ROHS</b> Compliant	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015