

126-03100



Article Number: 126-03100

Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag



Download drawing



Download spec sheet

## Base Data

<b>Local Order Number</b>	126-03100
<b>Type</b>	T50SOSSFT6.5E-MDL
<b>Color</b>	Green (GN)
<b>Features and Benefits</b>	This tie has an arrowhead design of fixing which offers a positive, low push-in force and a high pull-out force. When combined with the optional foam rubber seal it offers additional protection against the ingress of moisture or dirt.
<b>Product Description</b>	Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.
<b>Short Description</b>	Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag

## Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	200 N
<b>Length L (Imperial)</b>	6.3 "
<b>Length L (Metric)</b>	158.8 mm
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Length of Fir Tree</b>	7.0 mm
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.18 "
<b>Width W (Metric)</b>	4.6 mm
<b>Height H (Imperial)</b>	0.67 "
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.2 "
<b>Bundle Diameter Max. (Metric)</b>	30.0 mm
<b>Disc Diameter (Imperial)</b>	0.63 "
<b>Disc Diameter (Metric)</b>	16.0 mm
<b>Panel Thickness Max. (Imperial)</b>	0.07 "
<b>Panel Thickness Max. (Metric)</b>	1.8 mm
<b>Panel Thickness Min. (Imperial)</b>	0.02 "

<b>Panel Thickness Min. (Metric)</b>	0.6 mm		
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.26 "		
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.25 "	<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.26 "
			<b>Thickness T (Imperial)</b> 0.05 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	6.7 mm	<b>Mounting Hole Diameter D Min. (Metric)</b>	6.3 mm
<b>Thickness T (Metric)</b>	1.3 mm		

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500 Pieces
<b>Carton Quantity</b>	3000 Pieces
<b>Weight (Metric)</b>	2 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes