

151-00018



Article Number: 151-00018

Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00018

Type CTC10FT6LG

Color Black (BK)

- Features and Benefits**
- Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.
 - Extended fir tree allows for a wide range of panel thicknesses.
 - Fir tree design provides low insertion forces and high extraction forces.

Product Description Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

Short Description Convoluted Tubing Clip, Max Bundle Diameter .4", Panel Thickness .03"-.24", PA66HIRHS, Black, 500/pkg

Product Dimensions

Fixation Method Fir Tree

Width W (Imperial) 0.31 "

Width W (Metric) 8.0 mm

Height H (Imperial) 0.85 "

Height H (Metric) 21.4 mm

Height H2 (Imperial) 0.44 "

Height H2 (Metric) 11.1 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.03 "

Panel Thickness Max. (Metric) 6.0 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 0.75 mm

Mounting Hole Diameter D (Imperial) 0.26 - 0.28 "

Mounting Hole Diameter D (Metric) 6.5 - 7.0 mm

Mounting Hole Diameter D Min. (Imperial) 0.283 "

Mounting Hole Diameter D Max. (Imperial) 0.275 "

Nominal Diameter (Imperial) 3/8 "

Nominal Diameter (Metric) 10.0 mm

Mounting Hole Diameter D Max. (Metric) 7.0 mm

Mounting Hole Diameter D Min. (Metric) 6.5 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500 Pieces
Carton Quantity	5000 Pieces
Weight (Metric)	1 kg

Material and Specifications

Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes