

151-00080



Article Number: 151-00080

Bundling Clip, 1.7" Length, Panel Thickness 0.25" - 0.28", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 151-00080

**Type** COW30DP7

**Color** Black (BK)

- Features and Benefits**
- Clip can be installed by hand without the need for a tool.
  - Design provides low insertion force and high extraction force ideal for the production environment.
  - Clip secures bundle away from areas that can cause rubbing and chafing.

**Product Description** Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.

**Short Description** Bundling Clip, 1.7" Length, Panel Thickness 0.25" - 0.28", PA66HS, Black, 500/pkg

## Product Dimensions

**Length L (Imperial)** 1.7 "

**Length L2 (Imperial)** 1.2 "

**Fixation Method** Fir Tree

**Width W (Imperial)** 1.7 "

**Width W (Metric)** 42.0 mm

**Height H (Imperial)** 0.26 "

**Height H (Metric)** 6.6 mm

**Panel Thickness Max. (Imperial)** 0.18 "

**Panel Thickness Max. (Metric)** 4.5 mm

**Panel Thickness Min. (Imperial)** 0.03 "

**Panel Thickness Min. (Metric)** 0.8 mm

**Mounting Hole Diameter D (Imperial)** 0.25 - 0.28 "

**Mounting Hole Diameter D (Metric)** 6.3 - 7.0 mm

**Mounting Hole Diameter D Min. (Imperial)** 0.25 "

**Mounting Hole Diameter D Max. (Imperial)** 0.275 "

**Mounting Hole Diameter D Max. (Metric)** 7.0 mm  
6.3 mm

**Mounting Hole Diameter D Min. (Metric)**

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500

**Carton Quantity** 3000 Pieces

**Weight (Metric)** 2.35 kg

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes