

151-00623



Article Number: 151-00623

Standoff Tape Clip, Panel Thickness 0.03" - 0.22", PA66HIRHS, Black, 1.500/box



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00623
Type SOCHFT6
Color Black (BK)

Features and Benefits

- Staggered fir tree branch design provides low insertion forces and high extraction forces.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Product Description Stand Off Tape Clips provide unique mounting solutions for applications requiring two bundles to be separated from both mounting hoes and each other. Anti-sliding bars on the ends of the tape bar assist in preventing the tape from sliding off the clip in a high movement/vibration applications.

Short Description Standoff Tape Clip, Panel Thickness 0.03" - 0.22", PA66HIRHS, Black, 1.500/box

Product Dimensions

Length L (Imperial) 2.2 "

Length L (Metric) 56.0 mm

Length L2 (Imperial) 1.7 "

Length L2 (Metric) 42.5 mm

Fixation Method Fir Tree

Height H (Imperial) 0.9 "

Height H (Metric) 22.5 mm

Panel Thickness Max. (Imperial) 0.22 "

Panel Thickness Max. (Metric) 5.7 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.7 mm

Mounting Hole Diameter D (Imperial) 0.25 - 0.27 "

Mounting Hole Diameter D (Metric) 6.35 - 7.0 mm

Mounting Hole Diameter D Min. (Imperial) 0.27 "

Mounting Hole Diameter D Max. (Imperial) 0.25 "

Mounting Hole Diameter D Max. (Metric) 7.0 mm

6.35 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per box

Package Quantity (Metric) 1500

Carton Quantity 1500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)