

151-00785



Article Number: 151-00785



Download drawing



Download spec sheet

## Base Data

<b>Local Order Number</b>	151-00785
<b>Type</b>	CCFT6LG
<b>Color</b>	Black (BK)

**Features and Benefits** The cable bundle is fastened to the winder bar with cable ties or adhesive tape. It is routed above the connector clip.

The two TapeClip elements are used to clip connectors onto the cable set. The connector is fixed securely to the set and is protected against soiling. None of the elements are direction-specific.

## Product Dimensions

<b>Fixation Method</b>	Fir Tree
<b>Panel Thickness Max. (Imperial)</b>	0.16 "
<b>Panel Thickness Max. (Metric)</b>	4.0 mm
<b>Panel Thickness Min. (Imperial)</b>	0.03 "
<b>Panel Thickness Min. (Metric)</b>	0.7 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.24-0.26 "
<b>Mounting Hole Diameter D (Metric)</b>	6.0 - 6.7 mm
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.24 "
<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.26 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	6.7 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	6.0 mm

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Weight (Metric)</b>	0.8 kg

## Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes

