

151-00903



Article Number: 151-00903

Standoff Tape Clip, Panel Thickness 0.02" - 0.23", PA66HIRHS, Natural, 3,000/box



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00903

Type SOC10FT6LG

Color Natural (NA)

Features and Benefits

- Staggered fir tree branch design provides low insertion forces and high extraction forces.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Product Description Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using bundle or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standoff and stud mount versions.

Short Description Standoff Tape Clip, Panel Thickness 0.02" - 0.23", PA66HIRHS, Natural, 3,000/box

Product Dimensions

Length L (Imperial) 2.3 "

Length L (Metric) 58.0 mm

Length L2 (Imperial) 1.7 "

Length L2 (Metric) 43.4 mm

Width W (Imperial) 0.6 "

Width W (Metric) 16.0 mm

Height H (Imperial) 0.6 "

Height H (Metric) 14.5 mm

Panel Thickness Max. (Imperial) 0.23 "

Panel Thickness Max. (Metric) 6.0 mm

Panel Thickness Min. (Imperial) 0.02 "

Panel Thickness Min. (Metric) 0.6 mm

Mounting Hole Diameter D (Metric) 6.1 - 6.9 mm

Mounting Hole Diameter D Min.
(Imperial) 0.24 "

Mounting Hole Diameter D Max.0.27 "
(Imperial)

Mounting Hole Diameter D Max.6.9 mm
(Metric) 6.1 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per box

Package Quantity (Metric) 3000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes