

156-00067



Article Number: 156-00067

Heavy Duty Fir Tree Mount with Cable Tie, Panel Thickness 0.04" - 0.25", PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00067

**Type** T120RFT9A

**Color** Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
  - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
  - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

**Product Description** HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

**Short Description** Heavy Duty Fir Tree Mount with Cable Tie, Panel Thickness 0.04" - 0.25", PA66HIRHSUV, Black, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 535.0 N

**Length L (Imperial)** 15.0 "

**Length L (Metric)** 380.0 mm

**Length L2 (Imperial)** 0.9 "

**Length L2 (Metric)** 22.6 mm

**Fixation Method** Fir Tree

**Identification Plate Position** none

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Width W2 (Imperial)** 0.8 "

**Width W2 (Metric)** 20.3 mm

**Height H (Imperial)** 0.07 "

**Height H (Metric)** 1.8 mm

**Height H2 (Imperial)** 0.35 "

**Height H2 (Metric)** 9.0 mm

**Bundle Diameter Max. (Imperial)** 4.0 "

**Bundle Diameter Max. (Metric)** 100.0 mm

**Disc Diameter (Imperial)** 0.85 "

<b>Disc Diameter (Metric)</b>	21.6 mm
<b>Panel Thickness Max. (Imperial)</b>	0.25 "
<b>Panel Thickness Max. (Metric)</b>	6.5 mm
<b>Panel Thickness Min. (Imperial)</b>	0.04 "
<b>Panel Thickness Min. (Metric)</b>	1.0 mm
<b>Mounting Hole Diameter D (Metric)</b>	8.7 - 9.2 mm
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.34 "
	<b>Mounting Hole Diameter D Max.0.36 "</b>
	<b>(Imperial)</b>
	<b>Mounting Hole Diameter D Max.9.2 mm</b>
	<b>(Metric)</b> 8.7 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100
<b>Carton Quantity</b>	1000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes