

157-00035

Article Number: 157-00035

Wide Strap Tie with 0.3" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 157-00035

**Type** WSI8MM

**Color** Black (BK)

**Features and Benefits**

- Applies to threaded studs for quick and easy installation.
- Design of strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses.
- Strap is flexible and utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

**Product Description** The Wide Strap Heavy Duty Cable Tie features a stud mount for direct application onto a 8 mm threaded stud. The design of the strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses. The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. A thinner strap provides increased flexibility for improved ergonomics.

**Short Description** Wide Strap Tie with 0.3" Stud Mount, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 534 N

**Length L (Imperial)** 12.7 "

**Length L (Metric)** 322.6 mm

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Bundle Diameter Min. (Imperial)** 0.38 "

**Bundle Diameter Min. (Metric)** 9.5 mm

**Bundle Diameter Max. (Imperial)** 3.3 "

**Bundle Diameter Max. (Metric)** 82.5 mm

**Stud Size (Imperial)** 0.315 "

**Stud Size (Metric)** 8.0 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 300 Pieces

Carton Quantity 1200

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes