

157-00401



**Article Number:** 157-00401

**Wide Strap Tie with 0.25" Stud Mnt, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 157-00401

**Type** WSI250

**Color** Black (BK)

- Features and Benefits**
- Applies to threaded studs for quick and easy installation.
  - Design of strap minimizes pinching on soft bundles such as convoluted tubing or soft hoses.
  - Strap is flexible and utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

**Product Description** The Wide Strap Heavy Duty Cable Tie features a stud mount for direct application onto a 1/4" threaded stud. The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud. A thinner strap provides increased flexibility for improved ergonomics.

**Short Description** Wide Strap Tie with 0.25" Stud Mnt, 120 lbs, 12.7" Long, Width 0.5", PA66HIRHSUV, Black, 300/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 534 N

**Length L (Imperial)** 12.7 "

**Length L (Metric)** 322.6 mm

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Bundle Diameter Min. (Imperial)** 0.38 "

**Bundle Diameter Min. (Metric)** 9.5 mm

**Bundle Diameter Max. (Imperial)** 3.3 "

**Bundle Diameter Max. (Metric)** 82.5 mm

**Stud Size (Imperial)** 0.25 "

**Stud Size (Metric)** 6.35 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 300 Pieces

**Carton Quantity** 1200 Pieces

## **Material and Specifications**

---

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL94 HB

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

**ROHS Compliant** Yes