

170-03061



Article Number: 170-03061

Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 25.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03061

Type BSHTFG100

Color Black (BK)

- Features and Benefits**
- An extremely tough sleeveing material which provides thermal protection up to 1,200°F.
 - Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
 - Cuts easily with ordinary scissors for easy application.
 - UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

Product Description An extremely high-temperature resistant sleeveing designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.

Short Description Resin Coated Fiberglass Sleeveing, 1.0" Dia., Black, 25.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 25.0 ft

Length L (Metric) 7.62 m

Reel Length (imperial) 25.0 ft

Bundle Diameter Max. (Imperial) 1.625 "

Bundle Diameter Max. (Metric) 41.3 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 25 ft

Weight (Metric) 1.2 kg

Weight (imperial) 2.61 lbs

Material and Specifications

Material Glass Fiber (GF)

Operating Temperature -94°F to +1202°F (-70°C to +650°C)

ROHS Compliant Yes

UL Recognized (US) Yes

