HellermannTyton

170-03108



Article Number: 170-03108

Plenum Rated Expandable Braided Sleeving (Halar), 1.0" Dia., Black, 65.0 ft/Reel

RoHS





Base Data

Local Order Number 170-03108

Type BSHLR100

Color Black (BK)

Features and Benefits • Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.

• Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to

Cobal 60 radiation.

• Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Product Description Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the

primary concern.

Short Description Plenum Rated Expandable Braided Sleeving (Halar), 1.0" Dia., Black, 65.0 ft/Reel

Product Dimensions

Length L (Imperial) 65.0 ft

Length L (Metric) 19.8 m

Reel Length (imperial) 65.0 ft

Bundle Diameter Min. (Imperial) 0.63 "

Bundle Diameter Min. (Metric) 15.9 mm

Bundle Diameter Max. (Imperial) 1.63 "

Bundle Diameter Max. (Metric) 41.3 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 65 ft

Package Quantity (Metric) 65.0 ft

Weight (Metric) 0.65 kg

Weight (imperial) 1.43 lbs

Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1

FAR 25

Operating Temperature $-103^{\circ}\text{F to } +302^{\circ}\text{F } (-75^{\circ}\text{C to } +150^{\circ}\text{C})$

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes

© HellermannTyton 2015