

170-03182



Article Number: 170-03182

Split Wrap Woven Sleeveing, 0.5" ID, Polyester Blend, Black, 300.0 ft/Bulk Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03182

Type BSSWV120B

Color Black (BK)

- Features and Benefits**
- Center-slit overlapping design allows quick and easy access to the wires and cables for future maintenance or inspection without disassembly.
 - Flexible material allows it to easily wrap around a variety of component shapes and sizes, making it easier to use than slit-loom tubing or spiral-wrap materials.
 - A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris.
 - Overlapping design enhances flexibility, allowing it to shift and bend without exposing wire and cables.

Product Description Split Wrap Woven Sleeveing is a self-closing sleeveing manufactured from a unique blend of monofilament and multifilament polyester fibers that resemble a tightly woven material. The wrap around design provides increased flexibility, better coverage and greater resistance from abrasion for wires, cables and assemblies. Can also be used to reduce noise in applications that involve movement, while protecting sensitive electronics and communication systems from dust and debris.

Short Description Split Wrap Woven Sleeveing, 0.5" ID, Polyester Blend, Black, 300.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial) 300.0 ft

Length L (Metric) 91.4 m

Bundle Diameter Max. (Imperial) 0.5 "

Bundle Diameter Max. (Metric) 12.7 mm

Nominal Diameter (Imperial) 1/2 "

Nominal Diameter (Metric) 12.7 mm

Wall Thickness WT (Imperial) 0.027 "

Wall Thickness WT (Metric) 0.68 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 300 ft

Weight (imperial) 5.4 lbs

Weight (Metric) 2.45 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

© HellemannTyton 2015