# HellermannTyton

## 181-00026

101-00020

Article Number: 181-00026

Slotted Wall Wiring Duct, 3" X 2", Adhesive, PVC, Black, 120ft/Carton

# HellermannTyton

RoHS



#### Base Data

Local Order Number	181-00026
Туре	SLA3X2
Color	Black (BK)
Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li> </ul>
Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".
Short Description	Slotted Wall Wiring Duct, 3" X2", Adhesive, PVC, Black, 120ft/Carton

#### **Product Dimensions**

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	3.0 "
Width W (Metric)	76.2 mm
Width W2 (Imperial)	3.0 "
Width W2 (Metric)	76.2 mm
Width W3 (Imperial)	0.4 "
Width W3 (Metric)	10.2 mm
Width W4 (imperial)	1.0 "
Width W4 (metric)	25.4 mm
Width W5 (imperial)	1.62 "
Width W5 (metric)	41.1 mm
Width W6 (imperial)	1.0 "
Width W6 (metric)	25.4 mm
Height H (Imperial)	2.07 "
Height H (Metric)	52.6 mm
Mounting Hole Centers (Imperial)	4.0 "

### Logistics and Packaging

Quantity PercartonPackage Quantity120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

#### **Material and Specifications**

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015