HellermannTyton

181-00581

181-00581			
Ar	ticle Number: 181-00581		
Si	otted Wall Wiring Duct, 2" X 3", Adhesive, PVC, Black, 120ft/Carton		
	RoHS		
Download drawing Download spec sheet			
Base Data			
Local Order Number	181-00581		
Туре	SLA2X3		
Color	Black (BK)		
Features and Benefits	 Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection. 		
Product Description	ProDuct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each		

Product Description Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".

Short Description Slotted Wall Wiring Duct, 2" X 3", Adhesive, PVC, Black, 120ft/Carton

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	2.0 "
Width W (Metric)	50.8 mm
Width W2 (Imperial)	2.0 "
Width W2 (Metric)	50.8 mm
Width W3 (Imperial)	0.4 "
Width W3 (Metric)	10.2 mm
Width W4 (imperial)	1.0 "
Width W4 (metric)	25.4 mm
Width W5 (imperial)	2.6 "
Width W5 (metric)	66.0 mm
Width W6 (imperial)	0.5 "
Width W6 (metric)	12.7 mm
Height H (Imperial)	3.07 "
Height H (Metric)	77.9 mm
Mounting Hole Centers (Imperial)	4.0 "

Logistics and Packaging

Quantity PercartonPackage Quantity120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2015