

181-00619

Article Number: 181-00619

High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, Black, 120ft/Carton



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 181-00619

**Type** SLHD4X4

**Color** Black (BK)

- Features and Benefits**
- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
  - Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
  - Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, Black, 120ft/Carton

## Product Dimensions

**Length L (Imperial)** 6.0 ft

**Length L (Metric)** 1.83 m

**Width W (Imperial)** 4.0 "

**Width W (Metric)** 101.6 mm

**Width W2 (Imperial)** 4.0 "

**Width W2 (Metric)** 101.6 mm

**Width W3 (Imperial)** 0.16 "

**Width W3 (Metric)** 4.1 mm

**Width W4 (imperial)** 0.4 "

**Width W4 (metric)** 10.2 mm

**Width W5 (imperial)** 3.6 "

**Width W5 (metric)** 91.4 mm

**Width W6 (imperial)** 1.5 "

**Width W6 (metric)** 38.1 mm

**Height H (Imperial)** 4.07 "

**Height H (Metric)** 103.4 mm

**Mounting Hole Centers (Imperial)** 2.0 "

## Logistics and Packaging

**Quantity Per** carton

**Package Quantity** 120.0 ft

**Package Quantity (Metric)** 36.6 m

**Carton Quantity** 120.0 ft

## Material and Specifications

---

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** UL  
CSA

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No

**UL Recognized (US)** Yes