HellermannTyton

181-33022	
	Article Number: 181-33022
	Slotted Wall Wiring Duct, 3" X 3", Adhesive, PVC, White, 120ft/Carton
HellermannTyton	Y ROHS
Download drawing	wnload spec sheet
Base Data	
	Imber 181-33022 Tumo SLA2V2
	Type SLA3X3
	Color White (WH)
Features and Be	 nefits • Strong fingers prevent unwanted breaking. Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
Product Descri	iption Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wide opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".
Short Descri	iption Slotted Wall Wiring Duct, 3" X 3", Adhesive, PVC, White, 120ft/Carton
Product Dimensions	
Length L (Imp	erial) 6.0 ft
Length L (M	letric) 1.83 m
Width W (Imp	erial) 3.0 "
Width W (M	letric) 76.2 mm
Width W2 (Imp	verial) 3.0 "
Width W2 (M	letric) 76.2 mm
Width W3 (Imp	erial) 0.4 "
Width W3 (M	letric) 10.2 mm
Width W4 (imp	verial) 1.0 "
Width W4 (m	netric) 25.4 mm
Width W5 (imp	verial) 2.6 "
Width W5 (m	netric) 66.0 mm
Width W6 (imp	verial) 1.0 "
Width W6 (m	netric) 25.4 mm
Height H (Imp	erial) 3.07 "
	letric) 77.9 mm

Logistics and Packaging

Quantity PercartonPackage Quantity120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015