HellermannTyton

184-12001

Article Number: 184-12001

High Density Slotted Wall Wiring Duct, 1" X 2", Adhesive, PVC, Gray, 30ft/Box



RoHS



Base Data

Local Order Number 184-12001

Type SLHDA1X2

Color Gray (GY)

Features and Benefits • Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

· Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier

installation.

• Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to

accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to

standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily

accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" X2", Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 1.62 "

Width W5 (metric) 41.1 mm

Height H (Imperial) 2.07 "

Height H (Metric) 52.6 mm

Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification UL

CSA

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes