## HellermannTyton

184-13002		
	Article Number: 184-13002 High Density Slotted Wall Wiring Duct, 1" X 3", Adhesive, PVC, White, 30ft/Box	
HellermannTyton	<b>√</b> RoHS	
Download spec sheet		
ase Data		
Local Order Numb		
	pe SLHDA1X3	
	or White (WH)	
Features and Benef	<ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.</li> <li>Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li> <li>Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.</li> </ul>	
Product Description	on Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.	
Short Description	on High Density Slotted Wall Wiring Duct, 1" X 3", Adhesive, PVC, White, 30ft/Box	
Product Dimensions		
Length L (Imperia	al) 6.0 ft	
Length L (Metr	<b>ic)</b> 1.83 m	
Width W (Imperia	al) 1.0 "	
Width W (Metr	ic) 25.4 mm	
Width W2 (Imperia	al) 1.0 "	
Width W2 (Metr	ic) 25.4 mm	
Width W3 (Imperia	al) 0.16 "	
Width W3 (Metr	ic) 4.1 mm	
Width W4 (imperia	-0.04"	

Width W4 (metric)10.2 mmWidth W5 (imperial)2.6 "Width W5 (metric)66.0 mmHeight H (Imperial)3.07 "Height H (Metric)77.9 mmMounting Hole Centers (Imperial)2.0 "

## Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

## Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2015