HellermannTyton

IB4-15400 Article Number: 184-15400 Impose the tight colspan="2">Impose the tight colspan="2">Impose tight colspan="2"

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1.5" X4", Non-Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	1.5 "
Width W (Metric)	38.1 mm
Width W2 (Imperial)	1.5 "
Width W2 (Metric)	38.1 mm
Width W3 (Imperial)	0.16 "
Width W3 (Metric)	4.1 mm
Width W4 (imperial)	0.4 "
Width W4 (metric)	10.2 mm
Width W5 (imperial)	3.6 "
Width W5 (metric)	91.4 mm
Height H (Imperial)	4.07 "
Height H (Metric)	103.4 mm
Mounting Hole Centers (Imperial)	2.0 "

Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2015