

211-60050

Article Number: 211-60050

P Clamp, .39" Width, .32" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 211-60050

**Type** H4P

**Color** Black (BK)

**Features and Benefits**

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

**Product Description** HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

**Short Description** P Clamp, .39" Width, .32" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

## Product Dimensions

**Fixation Method** screw-hole

**Variant** Closed

**Width W (Imperial)** 0.39 "

**Width W (Metric)** 10.0 mm

**Bundle Diameter Max. (Imperial)** 0.32 "

**Bundle Diameter Max. (Metric)** 8.0 mm

**Mounting Hole Diameter D (Imperial)** 0.17 "

**Mounting Hole Diameter D (Metric)** 4.2 mm

**Nominal Diameter (Imperial)** 5/16 "

**Nominal Diameter (Metric)** 8 mm

**Wall Thickness WT (Imperial)** 0.047 "

**Wall Thickness WT (Metric)** 1.2 mm

**Mounting Hole Centers (Imperial)** 0.39 "

**Mounting Hole Diameter D Max.** 4.2 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 4.2 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 1000 Pieces

**Carton Quantity** 6000 Pieces

**Weight (Metric)** 0.5 kg

## Material and Specifications

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes