

## 3N0C



**Article Number:** 161-05050

**Spiralwrap, 1/2" Diameter, PA6, Black, 100ft/RL**



Download spec sheet

### Base Data

**Local Order Number** 3N0C

**Type** 3NOC-PA6-BK

**Color** Black (BK)

- Features and Benefits**
- Sheathing allows flexible routing and lead-out of cables
  - The inner edges are beveled preventing damage to cables
  - Sheathing is reusable and resistant to most chemicals
  - Spiralwrap is U.L. Recognized

**Product Description** HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

**Short Description** Spiralwrap, 1/2" Diameter, PA6, Black, 100ft/RL

### Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Variant** Spiral Binding

**Bundle Diameter Min. (Imperial)** 4.0 "

**Bundle Diameter Min. (Metric)** 102.0 mm

**Bundle Diameter Max. (Imperial)** 0.375 "

**Bundle Diameter Max. (Metric)** 9.52 mm

**Diameter D (imperial)** 0.5 "

**Diameter D (metric)** 12.7 mm

**Nominal Diameter (Imperial)** 1/2 "

**Nominal Diameter (Metric)** 12.7 mm

**Wall Thickness WT (Imperial)** 0.035 "

**Wall Thickness WT (Metric)** 0.89 mm

**Pitch (imperial)** 0.5 "

**Pitch (metric)** 12.7 mm

### Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100.0 ft

**Package Quantity (Metric)** 30.48 m

**Carton Quantity** 1200.0 ft

## Material and Specifications

---

|                              |                                   |
|------------------------------|-----------------------------------|
| <b>Material</b>              | Polyamide 6 (PA6)                 |
| <b>Material Shortcut</b>     | PA6                               |
| <b>Flammability</b>          | UL94 V2                           |
| <b>Operating Temperature</b> | -40°F to +250°F (-40°C to +121°C) |
| <b>ROHS Compliant</b>        | Yes                               |
| <b>UL Recognized (US)</b>    | Yes                               |