


553-50010

Article Number: 553-50010

Heat Shrink Label, .187" Unslit, Single Sided, Polyolefin, White, 1000/BX



Download spec sheet

## Base Data

**Local Order Number** 553-50010

**Type** HST4.8-1.6WH

**Color** White (WH)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** Heat Shrink Label, .187" Unslit, Single Sided, Polyolefin, White, 1000/BX

## Product Dimensions

**Length L (Imperial)** 1.9 "

**Length L (Metric)** 48.3 mm

**Printable (Yes/No)** Yes

**Variant** Thin-Wall

**Width W (Imperial)** 1.90 "

**Width W (Metric)** 48.2 mm

**Height H (Imperial)** 0.312 "

**Height H (Metric)** 7.9 mm

**Diameter Max. (Imperial)** 0.187 "

**Outside Diameter Max. (Imperial)** 0.187 "

**Wall Thickness WT (Imperial)** 0.028 "

**Wall Thickness WT (Metric)** 0.65 mm

**Print Method** Thermal Transfer

**Recovered Diameter d (metric)** 1.6 mm

**Recovered Diameter d (imperial)** 0.063 "

**Supplied Diameter D (imperial)** 0.177 "

**Supplied Diameter D (metric)** 4.8 mm

**Thickness T (Metric)** 3.0 µm

**Width of Liner WL (imperial)** 3.0 "

**Width of Liner WL (metric)** 76.2 mm

Width of printable area (metric) 48.26 mm

Width of Printable Area (imperial) 1.9 "

## Logistics and Packaging

---

**Quantity Per** box  
**Package Quantity** 1000  
**Package Quantity (Metric)** 1000  
**Markers per row** 1  
**Weight (Metric)** 0.635 kg  
**Weight (imperial)** 1.39 lbs

## Material and Specifications

---

**Material** Polyolefin, cross-linked (PO-X)  
**Material Shortcut** PO-X  
**US MILSPEC** SAE-AS81531  
AMS-DTL-23053/5 Class 1 and 3  
MIL-STD-202G Method 215K  
**Dielectric Strength (Metric)** 19.7 kV min.  
**Flammability** UL224 VW-1  
**Shrink Temperature** +194 °F (+90 °C)  
**Operating Temperature** -67°F to +275°F (-55°C to +135°C)  
**ROHS Compliant** Yes  
**Certification/Specification** MIL-STD-202G Method 215K  
UL224 125 °C 600V VW-1  
SAE-AS81531  
SAE - AMS - DTL-23053/5 Class 1 and 3