HellermannTyton

558-00328

Article Number: 558-00328

Banded Colored Continuous Roll, 2.0" X 250', PET, Yellow/White, 250ft/RL

✓ RoHS

📄 Download drawing   📄 Download spec sheet

Base Data

Local Order Number	558-00328
Type	HT2YE50250
Color	Yellow (YE)
Features and Benefits	• Continuous Colored Signal Panel labels come with yellow or orange stripes for easy printing of caution and warning labels. • Continuous labels allow for designing and cutting labels to any length. • Various widths are available so that a wide variety of sign sizes can be customized and produced on demand.
Product Description	The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Insitute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.
Short Description	Banded Colored Continuous Roll, 2.0" X 250', PET, Yellow/White, 250ft/RL

Product Dimensions

Length L (Imperial)	250.0 ft
Length L (Metric)	76.2 m
Width W (Imperial)	2.0 "
Width W (Metric)	50.8 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm
Print Method	Thermal Transfer
Vertical Repeat VR (metric)	50.8 mm
Vertical Repeat VR (imperial)	2.0 "
Width of Liner WL (imperial)	2.0 "
Width of Liner WL (metric)	50.8 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	250 ft
Package Quantity (Metric)	76.2 m
Labels per Column	1
Labels per Row	1

Material and Specifications

Material	Polyester (PET)

Material Shortcut	PET
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes

Material Shortcut	PET
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes