


596-00240

Article Number: 596-00240

Printable Solar Label, DC BACKUP SYSTEM LABEL, 4.0" X 2.00", Polyester, Red, 50/RL



Download spec sheet

Base Data

Local Order Number 596-00240
Type ACRATING
Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4" X2" White text on red background that reads as: "RATED AC OPERATING CURRENT; MAX RATED AC OPERATING CURRENT; RATED AC OPERATING VOLTAGE; MAX RATED AC OPERATING VOLTAGE; RATED SHORT CIRCUIT CURRENT; MAXIMUM SYSTEM VOLTAGE." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Short Description Printable Solar Label, DC BACKUP SYSTEM LABEL, 4.0" X2.00", Polyester, Red, 50/RL

Product Dimensions

Width W (Imperial) 4.0 "
Width W (Metric) 101.6 mm
Height H (Imperial) 2.0 "
Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per reel
Package Quantity 50
Package Quantity (Metric) 50

Material and Specifications

Material Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate
Material Shortcut 840/926
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)
Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes

Certification/Specification UL969

UL Recognized (US) Yes