## HellermannTyton

596-00427	
	ticle Number: 596-00427 re-Printed Header Label, CAUTION, 4'' X 6'', PET, Yellow, 250/RL
HellermannTyton ¥	RoHS
Download spec sheet	
Base Data	
Local Order Number	
Color Features and Benefits	Yellow (YE)
reatures and benefits	<ul> <li>Made with UV stable inks and materials for durability and weather resistance</li> <li>Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li> <li>High abrasion and scuff resistance for high performance labeling.</li> <li>Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections</li> </ul>
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electric Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Pre-Printed Header Label, CAUTION, 4" X6", PET, Yellow, 250/RL
Product Dimensions	
Length L (Imperial)	6.0 "
Length L (Metric)	152.4 m
Width W (Imperial)	4.0 "
Width W (Metric)	101.6 mm
Height H (Imperial)	6.0 "
Height H (Metric)	152.4 mm
ogistics and Packaging	
Quantity Per	reel
Package Quantity	250

Package Quantity (Metric) 250

## **Material and Specifications**

Material	Polyester (PET)
Material Shortcut	PET
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Halogenfree	Yes

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes

UL Recognized (US) Yes

© HellermannTyton 2015