

596-00504



Article Number: 596-00504

Foam Nameplate, 2.0" X 1.0" Rectangular Nameplate, PET, White, 500/RL



Download drawing



Download spec sheet

Base Data

Local Order Number 596-00504

Type NPL51X25WH

Color White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
 - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
 - Labels are UV and chemical resistant for long life in an industrial environment.
 - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

Product Description Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

Short Description Foam Nameplate, 2.0" X 1.0" Rectangular Nameplate, PET, White, 500/RL

Product Dimensions

Length L (Imperial) 1.0 "

Length L (Metric) 25.4 mm

Self adhesive (Yes/No) Yes

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Height H (Imperial) 1.0 "

Height H (Metric) 25.4 mm

Horizontal Repeat HR (imperial) 2 "

Horizontal Repeat HR (metric) 50.8 mm

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 1.125 "

Vertical Repeat VR (metric) 28.57 mm

Width of Liner WL (imperial) 2.2 "

Width of Liner WL (metric) 55.88 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 500

Package Quantity (Metric) 500

Weight (Metric) 0.22 kg
Weight (imperial) 0.5 lbs

Material and Specifications

Material Polyester (PET)
Material Shortcut PET
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +176°F (-40°C to +80°C)
Operating Temperature -40°F to +176°F (-40°C to +80°C)
ROHS Compliant Yes
UL Recognized (US) Yes