

596-00624

Article Number: 596-00624

Terminal Block Label, .275" wide, PE, White, 100ft/RL

HellermannTyton



Download spec sheet

## Base Data

**Local Order Number** 596-00624

**Type** TBL275

**Color** White (WH)

**Features and Benefits**

- Label stock for use with thermal transfer printers.
- Strong acrylic adhesive for industrial applications.
- Abrasion and chemical resistant top coat for long lasting results.
- For use with HellermannTyton thermal transfer printers or most standard brands.

**Product Description** To suit different industrial applications, HellermannTyton offers a wide variety of thermal transfer label stocks including polyester, metalized polyester, clear polyester, cloth, polyimide and Durattach high density polyolefin. Thermal transfer labels include a strong acrylic adhesive and abrasion and chemical resistant top coatings for long lasting results. Easily print custom labels and variable information with HellermannTyton TagPrint® Pro labeling software and a thermal transfer printer.

**Short Description** Terminal Block Label, .275" wide, PE, White, 100ft/RL

## Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Width W (Imperial)** 100.0 ft

**Width W (Metric)** 3048 mm

**Height H (Imperial)** 0.275 "

**Height H (Metric)** 6.98 mm

**Print Method** Thermal Transfer

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100

**Package Quantity (Metric)** 100

**Labels per Column** 1

**Labels per Row** 1

## Material and Specifications

**Material** Polyethylene (PE)

**Material Shortcut** PE

**Adhesive Operating Temperature** -40°F to +300°F (-40°C to +149°C)

**Halogenfree** Yes  
**Operating Temperature** -40°F to +300°F (-40°C to +149°C)  
**ROHS Compliant** Yes  
**UL Recognized (US)** Yes