

## CT1503X2



Article Number: 597-00033

Self-Laminating Tag, Generic Write-On, Blank Lines, 4.0" X 1.5", Orange, 25/pkg



Download spec sheet

### Base Data

**Local Order Number** CT1503X2

**Type** CT1503

**Color** Orange (OG)

**Features and Benefits**

- Clear laminating plastic flap permanently protects the writing and data marked on the tag.
- Mounting holes for easy mounting using standard cable ties.
- Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.

**Color Marking Field** Orange (OG)

**Product Description** HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

**Product Features**

- Easily and conveniently fits in a pants or shirt pocket.
- Once loaded, unit allows minimal label exposure to dust and moisture.
- Can be used with standard ball point pens or HellermannTyton nylon marking pens.
- Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit.
- The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.

**Short Description** Self-Laminating Tag, Generic Write-On, Blank Lines, 4.0" X 1.5", Orange, 25/pkg

### Product Dimensions

**Length L (Imperial)** 1.5 "

**Length L (Metric)** 38.1 mm

**Width W (Imperial)** 4.0 "

**Width W (Metric)** 101.6 mm

**Height H (Imperial)** 1.5 "

**Height H (Metric)** 38.1 mm

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 25

**Package Quantity (Metric)** 25

**Labels per Column** 1

**Labels per Row** 1

**Labels per Sheet** 1

## Material and Specifications

---

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Operating Temperature** -40°F to +266°F (-40°C to +130°C)

**ROHS Compliant** Yes