

Article Number: 597-00030

Caution Write-On Self-Laminating Tag, Fiber Optic Cable, 3.5" X 2.0", Orange, 25/pkg



Download spec sheet

Base Data

Local Order Number CT2003X2

Type CT2003

Color Orange (OG)

Features and Benefits

- Clear laminating plastic flap permanently protects the writing and data marked on the tag.
- Mounting holes for easy mounting using standard cable ties.
- Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.

Color Marking Field Orange (OG)

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Product Features

- Easily and conveniently fits in a pants or shirt pocket.
- Once loaded, unit allows minimal label exposure to dust and moisture.
- Can be used with standard ball point pens or HellermannTyton nylon marking pens.
- Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit.
- The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.

Short Description Caution Write-On Self-Laminating Tag, Fiber Optic Cable, 3.5" X 2.0", Orange, 25/pkg

Product Dimensions

Length L (Imperial) 2.0 "

Length L (Metric) 50.8 mm

Width W (Imperial) 3.5 "

Width W (Metric) 88.9 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

Horizontal Repeat HR (metric) 88.90 mm

Horizontal Repeat HR (imperial) 3.5 "

Vertical Repeat VR (metric) 50.8 mm

Vertical Repeat VR (imperial) 2.0 "

Logistics and Packaging

Quantity Per pack

Package Quantity 25

Package Quantity (Metric) 25

Labels per Column 1
Labels per Row 1
Labels per Sheet 1
Weight (Metric) 0.2 kg

Material and Specifications

Material Polyvinylchloride (PVC)
Material Shortcut PVC
Operating Temperature -40°F to +266°F (-40°C to +130°C)
ROHS Compliant Yes