

CTP140STD

Article Number: 169-60509

Convoluted Tubing, Slit, 1/4" Dia., PE, Black, 3200ft/Carton



Download drawing



Download spec sheet

Base Data

Local Order Number CTP140STD

Type CTP140

Color Black (BK)

Features and Benefits

- Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.
- Tubing provides full coverage where spiral wrap or other coverings may not be suitable.
- In harsh applications the tubing provides resistance to crushing, impact, and abrasion.
- Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Product Description HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description Convoluted Tubing, Slit, 1/4" Dia., PE, Black, 3200ft/Carton

Product Dimensions

Length L (Imperial) 3200.0 ft

Length L (Metric) 975.4 m

Inner Diameter D (Imperial) 0.276 "

Inner Diameter D (metric) 7.01 mm

Diameter D (imperial) 0.398 "

Diameter D (metric) 10.11 mm

Diameter D2 (imperial) 0.276 "

Diameter D2 (metric) 7.01 mm

Diameter D3 (metric) 7.01 mm

Outside Diameter D (imperial) 0.398 "

Outside Diameter D (metric) 10.11 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.35 mm

Wall Thickness WT (Imperial) 0.004 "

Wall Thickness WT (Metric) 0.102 mm

Logistics and Packaging

Quantity Per carton

Package Quantity 3200.0 ft

Package Quantity (Metric) 975.4 m

Carton Quantity 3200

Material and Specifications

Material Polyethylene (PE)

Material Shortcut PE

Flammability UL94 HB

Operating Temperature -40°F to +199°F (-40°C to +93°C)

ROHS Compliant Yes