

## FC1.2AK2

**Article Number:** 154-00013

**Flat Ribbon Adhesive Clamp, 1.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg**



Download spec sheet

### Base Data

**Local Order Number** FC1.2AK2  
**Type** FC1.2A  
**Color** Gray (GY)

**Features and Benefits**

- Adjustable height feature allows the clamp to close to the exact height of the ribbon cable.
- Releasable for easy access to cables when necessary.
- Available in adhesive or screw mount versions.

**Product Description** HellermannTyton's flat ribbon clamps route, protect and secure flat ribbon cables without damage to sensitive wires and cables. The unique, adjustable height feature allows the clamp to close to the exact height of the ribbon cable, using only as much force as needed to secure the cable. The releasable feature allows simple opening when access to the cable is necessary. These clamps are available in adhesive or screw mount versions.

**Short Description** Flat Ribbon Adhesive Clamp, 1.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg

### Product Dimensions

**Length L (Imperial)** 0.75 "

**Length L (Metric)** 19.0 mm

**Width W (Imperial)** 1.5 "

**Width W (Metric)** 38.1 mm

**Height H (Imperial)** 0.5 "

**Height H (Metric)** 12.7 mm

**Mounting Hole Diameter D (Imperial)** 0.156 "

**Mounting Hole Diameter D (Metric)** 4.0 mm

**For Cable Width Max. (Metric)** 30.48 mm

**For Cable Width Max. (Imperial)** 1.2 "

**Mounting Hole Diameter D Max. (Metric)** 4.0 mm

**Mounting Hole Diameter D Min. (Metric)** 4.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 50 Pieces

**Carton Quantity** 50

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Acrylate with base of polyurethane foam

**Adhesive Operating Temperature** to +230°F (+110°C)

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes