

HDM500BHIHSUVC2

Article Number: 151-00446

High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number HDM500BHIHSUVC2

Type HDM500

Color Black (BK)

Features and Benefits

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

Product Description This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

Fixation Method (FF) Screw Mounting and Rivet

Short Description High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Length L (Imperial) 1.9 "

Length L (Metric) 47.0 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.5 "

Mounting Hole Diameter D (Metric) 12.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 500

Weight (Metric) 15.56 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Maximum Torque (kgf-cm) 1576 kgf-cm

Maximum Torque (lbf-ft) 114 lbf-ft

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes

© HellemannTyton 2015