HellermannTyton

MCRFW-EC



Article Number: 250-00014

InfoStream Multi-Channel Raceway End Cap, HIPS, Office White, 1/pkg

N RoH



Base Data

Local Order Number MCRFW-EC

Type MCR-EC

Color Office White (OEWH)

Features and Benefits • Raceway and fittings are manufactured from a UL 94V-0 rated material to insure compliance with codes

 $\bullet \ \text{All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII f$

standard

• Raceway and fittings are U.L. Listed to 600 Volts to meets new UL5A and CSA 22.2 No. 62-93 standards

· Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables

Product Description HellermannTyton's InfoStream non-metallic raceway system can accommodate up to four separate channels of

electrical, voice, data, video or fiber optic cabling. The elliptical shape is aesthetically pleasing when compared to

other designs. The raceway's unique and patented design make installations quicker and easier.

Short Description InfoStream Multi-Channel Raceway End Cap, HIPS, Office White, 1/pkg

Product Dimensions

Logistics and Packaging

Quantity Per bag

Package Quantity 1

Package Quantity (Metric) 1

Carton Quantity 100

Material and Specifications

Material Polystyrene, high impact resistant (PS-HIR)

Material Shortcut HIPS

ROHS Compliant Yes