

RT250S9X2



Article Number: 131-75819

Releasable Cable Tie, 9.1" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number RT250S9X2

Type RT250S

Color Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
 - Head design provides high tensile strength with very low insertion force even after repeated use.
 - Buckle feature on head allows excess strap to be tucked away after installation.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Releasable Cable Tie, 9.1" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1115.0 N

Length L (Imperial) 9.1 "

Length L (Metric) 230.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure Yes

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.49 "

Width W (Metric) 12.5 mm

Bundle Diameter Min. (Imperial) 0.47 "

Bundle Diameter Min. (Metric) 12.0 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 50.0 mm

Thickness T (Imperial) 0.075 "

Cable Tie Head Length (Imperial) 0.88 "

Cable Tie Head Width (Imperial) 0.79 "

Thickness T (Metric) 1.9 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 25 Pieces
Carton Quantity 1000
Weight (Metric) 6.6 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes
Certification/Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes