

RT50S0C2



Article Number: 115-06300

Releasable Cable Tie, 6.5" Long, 50 lb Tensile Strength, PA66, Black, 100/pkg



[Download spec sheet](#)

Base Data

Local Order Number RT50S0C2

Type RT50S

Color Black (BK)

Features and Benefits The extended pawl allows for simple and quick release of the ties.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Releasable Cable Tie, 6.5" Long, 50 lb Tensile Strength, PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 6.5 "

Length L (Metric) 165.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure Yes

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.055 "

Height H (Metric) 1.4 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.38 "

Bundle Diameter Max. (Metric) 35.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 5000

Weight (Metric) 1.2 kg

Material and Specifications

| | |
|--------------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |
| Certification/Specification | UL |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | Yes |