

## T120I0HSH4



**Article Number:** 111-12216

**Heavy Duty Cable Tie, 11.8" Long, 120lb Tensile Strength, PA66HS, Black, 500/pkg**



Download spec sheet

### Base Data

**Local Order Number** T120I0HSH4

**Type** T120I

**Color** Black (BK)

- Features and Benefits**
- Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 11.8" Long, 120lb Tensile Strength, PA66HS, Black, 500/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 535.0 N

**Length L (Imperial)** 11.8 "

**Length L (Metric)** 300.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Cable Tie Width Max. (Imperial)** 0.3 "

**Cable Tie Width Max. (Metric)** 7.61 mm

**Bundle Diameter Min. (Imperial)** 0.2 "

**Bundle Diameter Min. (Metric)** 5.0 mm

**Bundle Diameter Max. (Imperial)** 3.2 "

**Bundle Diameter Max. (Metric)** 80.0 mm

**Cable Tie Head Length (Imperial)** 0.393 "

**Cable Tie Head Width (Imperial)** 0.502 "

### Logistics and Packaging

**Quantity Per** bag  
**Package Quantity (Metric)** 500  
**Carton Quantity** 1000

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)  
**Material Shortcut** PA66HS  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40°F to +257°F (-40°C to +125°C)  
**ROHS Compliant** Yes  
**Certification/Specification** UL-ZODZ2.E64139  
**UL Listed (US and Canada)** Yes  
**UL Recognized (US and Canada)** Yes