

T120R0UVH4



Article Number: 111-12063

Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66UV, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T120R0UVH4

Type T120R

Color Black (BK)

Features and Benefits

- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66UV, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 535.0 N

Length L (Imperial) 15.2 "

Length L (Metric) 387.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.6 mm

Bundle Diameter Min. (Imperial) 0.2 "

Bundle Diameter Min. (Metric) 5.0 mm

Bundle Diameter Max. (Imperial) 4.1 "

Bundle Diameter Max. (Metric) 105.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 1000

Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
US MILSPEC	MS3367-3-0
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	Cage Code 53421 SAE - AS33671 UL-ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No