

## T250I9X2



**Article Number:** 111-25219

**Heavy Duty Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg**



Download spec sheet

### Base Data

**Local Order Number** T250I9X2

**Type** T250I

**Color** Natural (NA)

**Features and Benefits**

- Heavy duty design to offer higher tensile strength.
- Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 250.0 lbs

**Minimum Tensile Strength (Metric)** 1115.0 N

**Length L (Imperial)** 28.7 "

**Length L (Metric)** 730.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Variant** Inside Serrated

**Width W (Imperial)** 0.49 "

**Width W (Metric)** 12.5 mm

**Bundle Diameter Min. (Imperial)** 0.47 "

**Bundle Diameter Min. (Metric)** 12.0 mm

**Bundle Diameter Max. (Imperial)** 8.0 "

**Bundle Diameter Max. (Metric)** 203.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 25 Pieces

**Carton Quantity** 500

**Weight (Metric)** 17.6 kg

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes