

T30RA30



Article Number: 103-00002

Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number	T30RA30
Type	T30RA
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs. • Available in reels of 3,000 each or bandoliers of 30 each.
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Short Description	Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	30.0 lbs
Minimum Tensile Strength (Metric)	135.0 N
Length L (Imperial)	6.0 "
Length L (Metric)	152.0 mm
Cycle Time	1.2 seconds
Identification Plate Position	none
Reel Diameter (Metric)	450 mm
Reel Diameter (Imperial)	17.7 "
Reel Width (Metric)	182.8 m
Reel Width (Imperial)	7.197 "
Releasable Closure	No
Voltage Range	27 Volt
Width W (Imperial)	0.14 "
Width W (Metric)	3.6 mm
Bundle Diameter Min. (Imperial)	0.06 "
Bundle Diameter Min. (Metric)	1.5 mm
Bundle Diameter Max. (Imperial)	1.25 "
Bundle Diameter Max. (Metric)	31.0 mm
Power Supply	Electrical
Tension Force	Adjustable

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 600
Carton Quantity 6000
Reel Weight (Metric) 3.175 kg
Reel Weight (Imperial) 7 lbs
Weight (imperial) 3.9 lbs

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
US MILSPEC MS3367-5-9
Flammability UL94 V2
Operating Temperature -40°F to +185°F (-40°C to +85°C)
Certification/Specification Cage Code 53421
SAE - AS33671
UL-ZODZ2.E64139
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes