

## T30RA300HS



Article Number: 103-00003

Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg



Download spec sheet

### Base Data

<b>Local Order Number</b>	T30RA300HS
<b>Type</b>	T30RA
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.</li> <li>• Available in reels of 3,000 each or bandoliers of 30 each.</li> </ul>
<b>Product Description</b>	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
<b>Short Description</b>	Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	30.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	135.0 N
<b>Length L (Imperial)</b>	6.0 "
<b>Length L (Metric)</b>	152.0 mm
<b>Cycle Time</b>	1.2 seconds
<b>Identification Plate Position</b>	none
<b>Reel Diameter (Metric)</b>	450 mm
<b>Reel Diameter (Imperial)</b>	17.7 "
<b>Reel Width (Metric)</b>	182.8 m
<b>Reel Width (Imperial)</b>	7.197 "
<b>Releasable Closure</b>	No
<b>Voltage Range</b>	27 Volt
<b>Width W (Imperial)</b>	0.14 "
<b>Width W (Metric)</b>	3.6 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.25 "
<b>Bundle Diameter Max. (Metric)</b>	31.0 mm
<b>Thickness T (Imperial)</b>	0.05 "
<b>Power Supply</b>	Electrical
<b>Tension Force</b>	Adjustable
<b>Thickness T (Metric)</b>	1.2 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	600
<b>Carton Quantity</b>	6000
<b>Reel Weight (Imperial)</b>	7 lbs
<b>Reel Weight (Metric)</b>	3.175 kg
<b>Weight (imperial)</b>	3.9 lbs

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +275°F (-40°C to +135°C)
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes