

T30RSF0C2

Article Number: 126-00700

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RSF0C2

Type T30RSF(U)

Color Black (BK)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
 - Push mount style creates low insertion and high extraction force.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 6.3 "

Length L (Metric) 161.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 31.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.4 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 0.9 mm

Mounting Hole Diameter D (Imperial) 0.19 - 0.22 "

Mounting Hole Diameter D (Metric) 4.7 - 5.5 mm

Mounting Hole Diameter D Min. 0.19 "
(Imperial)

Mounting Hole Diameter D Max. 0.22 "
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 5.6 mm
(Metric)

Mounting Hole Diameter D Min. (Metric) 4.8 mm

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes