

T50SL6.NN6P

Article Number: 111-85469

Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number T50SL6.NN6P

Type T50SL6

Color Natural (NA)

Features and Benefits

- Wing design helps stabilize the tie in high vibration applications
- Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.
- Design of tie provides low insertion and high extraction force.

Product Description Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

Short Description Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.5 "

Length L (Metric) 165 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Width W2 (Imperial) 0.73 "

Width W2 (Metric) 18.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 34.0 mm

Disc Diameter (Imperial) 0.73 "

Disc Diameter (Metric) 18.5 mm

Panel Thickness Max. (Imperial) 0.1 "

Panel Thickness Max. (Metric) 2.5 mm

Panel Thickness Min. (Imperial) 0.02 "

| | | | |
|---|--------------|---|-------------------------------------|
| Panel Thickness Min. (Metric) | 0.5 mm | | |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.3 " | | |
| Mounting Hole Diameter D (Metric) | 6.3 - 7.5 mm | | |
| Mounting Hole Diameter D Min. (Imperial) | 0.25 " | Mounting Hole Diameter D Max.0.3 " | Thickness T (Imperial)0.05 " |
| | | (Imperial) | |
| Mounting Hole Diameter D Max. (Metric) | 7.5 mm | | |
| | | Mounting Hole Diameter D Min. (Metric)6.3 mm | |
| Thickness T (Metric) | 1.2 mm | | |

Logistics and Packaging

| | |
|----------------------------------|------|
| Quantity Per | bag |
| Package Quantity (Metric) | 500 |
| Carton Quantity | 4000 |

Material and Specifications

| | |
|------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |