

T5D05000M4



Article Number: 211-00125

P Clamp, .5" Width, .5" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg



Download spec sheet

Base Data

| | |
|------------------------------|---|
| Local Order Number | T5D05000M4 |
| Type | T5D0500 |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none"> • Easily guide and locate wire and cables up to 1.5" in diameter. • Designed with a radiused edge to prevent chaffing and cutting into insulation. |
| Product Description | HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1.5" bundle diameters. |
| Short Description | P Clamp, .5" Width, .5" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg |

Product Dimensions

| | |
|---|------------|
| Fixation Method | screw-hole |
| Variant | Closed |
| Width W (Imperial) | 0.5 " |
| Width W (Metric) | 12.7 mm |
| Bundle Diameter Max. (Imperial) | 0.5 " |
| Bundle Diameter Max. (Metric) | 12.7 mm |
| Mounting Hole Diameter D (Imperial) | 0.203 " |
| Mounting Hole Diameter D (Metric) | 5.1 mm |
| Wall Thickness WT (Imperial) | .050 " |
| Wall Thickness WT (Metric) | 1.3 mm |
| Mounting Hole Centers (Imperial) | 0.595 " |
| Mounting Hole Diameter D Max. (Metric) | 5.1 mm |
| Mounting Hole Diameter D Min. (Metric) | 5.1 mm |

Logistics and Packaging

| | |
|----------------------------------|-------------|
| Quantity Per | bag |
| Package Quantity (Metric) | 1000 Pieces |

Material and Specifications

| | |
|------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |

UL Recognized (US and Canada) Yes

© HellemanTyton 2015