

T5D07500M4



Article Number: 211-00127

P Clamp, .5" Width, .75" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg



Download spec sheet

Base Data

Local Order Number	T5D07500M4
Type	T5D0750
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Easily guide and locate wire and cables up to 1.5" in diameter. • Designed with a radiused edge to prevent chaffing and cutting into insulation.
Product Description	HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1.5" bundle diameters.
Short Description	P Clamp, .5" Width, .75" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg

Product Dimensions

Fixation Method	screw-hole
Variant	Closed
Width W (Imperial)	0.5 "
Width W (Metric)	12.7 mm
Bundle Diameter Max. (Imperial)	0.75 "
Bundle Diameter Max. (Metric)	19.05 mm
Mounting Hole Diameter D (Imperial)	0.203 "
Mounting Hole Diameter D (Metric)	5.1 mm
Wall Thickness WT (Imperial)	.050 "
Wall Thickness WT (Metric)	1.3 mm
Mounting Hole Centers (Imperial)	0.78 "
Mounting Hole Diameter D Max. (Metric)	5.1 mm
Mounting Hole Diameter D Min. (Metric)	5.1 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	1000 Pieces

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes