## HellermannTyton

## TAG11T4-822C Article Number: 596-00003 Thermal Transfer Label, .65" X .2", 4 Across, Polyester, White, 5000/RL RoHS HellermannTyton Download spec sheet **Base Data** Local Order Number TAG11T4-822C Type TAG11T4 Color Clear (CL) Features and Benefits • Thermal transfer labels are made with high performance materials for long term industrial applications. · Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. • The labels are available in a wide variety of sizes so that finding a label for a particular application is easy. Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core. Short Description Thermal Transfer Label, .65" X.2", 4 Across, Polyester, White, 5000/RL **Product Dimensions** Width W (Imperial) 0.65 " Width W (Metric) 16.5 mm Height H (Imperial) 0.20 " Height H (Metric) 5.08 mm Horizontal Repeat HR (metric) 16.5 mm Horizontal Repeat HR (imperial) 0.65 " Print Method Thermal Transfer Vertical Repeat VR (imperial) 0.30 " Vertical Repeat VR (metric) 7.62 mm Width of Liner WL (metric) 66.04 mm

## Logistics and Packaging

Quantity Per	reel
Package Quantity	5000
Package Quantity (Metric)	5000
Labels per Row	4

Width of Liner WL (imperial) 2.60 "

## Material and Specifications

MaterialType 822C, Clear Polyester (CL)Material Shortcut822C

Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	UL-Recognized

© HellermannTyton 2015