# HellermannTyton

## TAG16T3-DTH

Article Number: 596-00034

Thermal Transfer Label, .90" X .25", 3 Across, DTH, White, 10000/RL



RoHS



### **Base Data**

Local Order Number TAG16T3-DTH

Type TAG16T3 Color White (WH)

Features and Benefits • Thermal transfer labels are made with high performance materials for long term industrial applications.

• Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the

need to be dedicated to one printer model.

• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product

is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, .90" X.25", 3 Across, DTH, White, 10000/RL

## **Product Dimensions**

Width W (Imperial) 0.90 "

Width W (Metric) 22.86 mm

Height H (Imperial) 0.25 "

Height H (Metric) 6.35 mm

Horizontal Repeat HR (metric) 22.86 mm

Horizontal Repeat HR (imperial) 0.9 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 0.35 "

Vertical Repeat VR (metric) 8.89 mm

Width of Liner WL (metric) 85.09 mm

Width of Liner WL (imperial) 3.35 "

### **Logistics and Packaging**

Quantity Per reel

Package Quantity 10000

Package Quantity (Metric) 10000

Labels per Row 3

## **Material and Specifications**

Material Type DTH, Durattach white (WH)

Material Shortcut DTH

Adhesive Shortcut Acrylic

Adhesive Operating Temperature  $-40^{\circ}F$  to +140°F (-40°C to +60°C)

Operating Temperature  $-40^{\circ}\text{F} \text{ to } +140^{\circ}\text{F} \text{ (-}40^{\circ}\text{C to } +60^{\circ}\text{C)}$ 

ROHS Compliant Yes