HellermannTyton

TAG27T1-795	
A	rticle Number: 596-27795
т	hermal Transfer Label, 1.5" X .75", 1 Across, Polyester, Silver, 3000/RL
Download drawing	d spec sheet
Base Data	
Local Order Number	TAG27T1-795
Туре	TAG27T1
Color	Silver (SR)
Features and Benefits	 Thermal transfer labels are made with high performance materials for long term industrial applications. Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the
	need to be dedicated to one printer model.
	• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and
	abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The produc
Short Description	is supplied on rolls on a 3" cardboard core. Thermal Transfer Label, 1.5" X.75", 1 Across, Polyester, Silver, 3000/RL
Short Description	
Product Dimensions	
Width W (Imperial)	1.50 "
Width W (Metric)	38.11 mm
Height H (Imperial)	0.75 "
Height H (Metric)	19.05 mm
Horizontal Repeat HR (metric)	
Horizontal Repeat HR (imperial)	
Print Method	
Vertical Repeat VR (imperial)	
Vertical Repeat VR (metric)	
Width of Liner WL (metric)	
Width of Liner WL (imperial)	2.20 "
Logistics and Packaging	

Quantity Per	reel
Package Quantity	3000
Package Quantity (Metric)	3000
Carton Quantity	3000 Pieces
Labels per Row	1
Weight (Metric)	0.232 kg

Material	Type 795, Polyester, silver matt (SR)
Material Shortcut	795
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +300°F (-40°C to +149°C)
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015