## HellermannTyton

	diala Number 500 00050
	rticle Number: 596-28250
Т	nermal Transfer Label, .8" X 1.43", 4 Across, Cloth, White, 5000/RL
HellermannTyton	RoHS
Later Download drawing Download	d spec sheet
Base Data	
Local Order Number	TAG28T4-250
Туре	TAG28T4
Color	White (WH)
Features and Benefits	
	<ul> <li>Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating th need to be dedicated to one printer model.</li> </ul>
	• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Description	
	cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product
	is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, .8" X 1.43", 4 Across, Cloth, White, 5000/RL
Product Dimensions	
Width W (Imperial)	0.80 "
Width W (Metric)	20.3 mm
Height H (Imperial)	1.43 "
Height H (Metric)	36.3 mm
Horizontal Repeat HR (metric)	20.3 mm
Horizontal Repeat HR (imperial)	0.80 "
Print Method	Thermal Transfer
Vertical Repeat VR (imperial)	1.62 "
Vertical Repeat VR (metric)	41.1 mm
Width of Liner WL (metric)	87.6 mm
Width of Liner WL (imperial)	3.45 "
Logistics and Packaging	
Quantity Per	real

reel
5000
5000
5000 Pieces
4

## **Material and Specifications**

Material Shortcut	250
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
<b>ROHS</b> Compliant	Yes

© HellermannTyton 2015