

## TAG38T4-100B

Article Number: 596-00011

Thermal Transfer Self-Laminating Label, 1.0" X 1.5" X 7.37", 4 Across, Vinyl, White, 1000/RL



Download spec sheet

### Base Data

<b>Local Order Number</b>	TAG38T4-100B
<b>Type</b>	TAG38T4
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.</li><li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li><li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li><li>• HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.</li></ul>
<b>Color Marking Field</b>	White (WH)
<b>Product Description</b>	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
<b>Short Description</b>	Thermal Transfer Self-Laminating Label, 1.0" X 1.5" X 7.37", 4 Across, Vinyl, White, 1000/RL

### Product Dimensions

<b>Length L (Imperial)</b>	7.35 "
<b>Length L (Metric)</b>	188.9 mm
<b>Width W (Imperial)</b>	1.0 "
<b>Width W (Metric)</b>	25.4 mm
<b>Height H (Imperial)</b>	7.35 "
<b>Height H (Metric)</b>	188.9 mm
<b>Height H2 (Imperial)</b>	7.347 "
<b>Height H2 (Metric)</b>	186.6 mm
<b>Height of printable area (imperial)</b>	1.50 "
<b>Height of printable area (metric)</b>	38.1 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.81 "
<b>Bundle Diameter Min. (Metric)</b>	20.8 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.87 "
<b>Bundle Diameter Max. (Metric)</b>	47.5 mm
<b>Horizontal Repeat HR (imperial)</b>	1.0 "
<b>Horizontal Repeat HR (metric)</b>	25.4 mm
<b>Print Method</b>	Thermal Transfer

<b>Thickness T (Metric)</b>	25 µm
<b>Vertical Repeat VR (imperial)</b>	7.75 "
<b>Vertical Repeat VR (metric)</b>	196.80 mm
<b>Width of Liner WL (imperial)</b>	4.10 "
<b>Width of Liner WL (metric)</b>	104.14 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Carton Quantity</b>	1000
<b>Labels per Row</b>	4
<b>Weight (Metric)</b>	0.1 kg

## Material and Specifications

---

<b>Material</b>	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized